

## HYFIRE® 6 SERIES

### HYFIRE® 6-AL2 Digital CD Ignition

**Features At A Glance:**

- High output multi-spark ignition system
- Digital performance at analog prices
- 2 Stage built-in easy-to-adjust digital rev limiter – 1,000 to 9,900 RPM – no chips required!
- Latest microprocessor-controlled circuitry
- Easy to install
- Lightweight aluminum housing – maximum heat transfer
- More performance and lower power draw
- Quicker acceleration and throttle response
- Works with points, OEM or aftermarket electronic ignition, or magnetic crank triggers (exc. hall effect)



HYFIRE® 6 AL2 Digital CD Ignition. . . . . 6861M



<i>Mallory #6861M HYFIRE 6AL2</i>	<i>Product Feature Comparison</i>	<i>MSD #6421 6AL2</i>
Digital	Digital or Analog	Digital
Yes	Multiple Spark	Yes
Two Stages- No Chips Required	Rev Limiting	Two Stage
520	Primary Output Voltage	535
45,000	Secondary Voltage Output	45,000
135 mJ	Spark Energy	135 mJ
.6 Amps	Current Draw Per 1,000 RPM	.7 Amps
8-16	Operating Voltage Required	12-18
29440 / 29625 / 30440 / 30625	Recommended Coil	8252
4 - 6 - 8	Number of Cylinders	4 - 6 - 8
Extruded Aluminum	Housing Construction	Cast Aluminum